**GENESIS SOLAR WIND ARRAY COLLECTOR CATALOGING STATUS.** P. J. Burkett<sup>1</sup>, M.C. Rodriguez<sup>2</sup>, M.C. Calaway<sup>1</sup>, J.H. Allton<sup>3</sup>: (1) Jacobs (ESCG) at NASA Johnson Space Center, Houston, TX; (2) Geocontrol Systems (ESCG) at NASA Johnson Space Center, Houston, TX; (3) NASA, Johnson Space Center, Houston, TX; patti.j.burkett@nasa.gov.

**Introduction**: Genesis solar wind array collectors were fractured upon landing hard in Utah in 2004. The fragments were retrieved from the damaged canister, imaged, repackaged and shipped to the Johnson Space Center curatorial facility [1]. As of January 2009, the collection consists of 3460 samples. Of these, 442 are comprised into "multiple" sample groupings, either affixed to adhesive paper (177) or collected in jars (17), culture trays (87), or sets of polystyrene vials (161). A focused characterization task was initiated in May 2008 to document the largest samples in the collection. The task consisted of two goals: to document sapphire based fragments greater than 2 cm in one dimension, and to document silicon based fragments greater than 1 cm in one direction.

Sapphire-based	<b>Abbreviation</b>
Aluminum-on-sapphire	AlOS
Gold-on-sapphire	AuOS
Silicon-on-sapphire	SOS
Sapphire	SAP
Carbon-cobalt-gold-on-sapphire	CCoAuOS
Silicon-based	
Float-zone silicon	Si-FZ
Czochralski silicon	Si-CZ
Diamond-like carbon on silicon	DOS

**Cataloging technique:** Samples are handled cleanly with stainless steel tweezers for initial extraction from Utah packaging. Solar wind regime (space-craft array location) is determined by measuring fragment thickness on a Mitutoyo digimatic indicator.

Solar Wind Regime[2]	Array Location
Bulk	B/C
Coronal Mass Ejection	Е
High Speed	Н
Low Speed interstream	L

If the fragment is silicon-based, an FT-IR (Fourier transform infrared spectroscopy) is used for interferogram analysis to differentiate FZ and CZ silicon species. Lastly, an overview image is taken of the fragment to document basic surface condition using a Leica MZ9 stereomicroscope. Length, width, and area measurements are processed outside of the lab using Canvas X image analysis software.

IATERIAL AND REGIME	TOTAL SAMPLES	100 mm²	101 - 299 mm²	300 mm²
	104	20.2 %	52.9%	Λ1 26.9 %
B/C	104	20.2 /0	52.770	20.770
AIOS E	42	9.5 %	47.6%	42.9 %
AIOS H	39	17.9 %	43.6%	38.5 %
AIOS L	23	13.0 %	43.5%	43.5 %
AuOS	88	25.0 %	47.7%	27.3 %
B/C				
AuOS E	73	8.2 %	47.9%	43.8 %
AuOS H	64	9.4 %	46.9%	43.8 %
AuOS L	26	11.5 %	61.5 %	26.9 %
SOS B/C	79	30.4 %	38.0 %	34.2 %
SOS E	42	7.1 %	47.6 %	40.5 %
SOS H	34	2.9 %	38.2 %	50.0 %
SOS L	32	6.3 %	53.1 %	37.5 %
SAP B/C	23	47.8 %	26.1 %	26.1 %
SAP E	35	20.0 %	37.1 %	42.9 %
SAP H	28	10.7 %	39.3 %	50.0 %
SAP L	14	28.6 %	50.0 %	21.4 %
CCo-	6	-	66.7 %	33.3 %
AuOS				
B/C			< <b>-</b> 0 (	
Si B/C	15	93.3 %	6.7 %	-
Si E	8	87.5 %	12.5 %	-
Si H	28	60.7 %	39.3 %	-
Si L	2	100.0 %	-	-
Si-FZ B/C	111	94.6 %	5.4 %	-
Si-FZ E	42	95.2 %	4.8 %	-
Si-FZ H	27	88.9 %	11.1%	-
Si-FZ L	24	95.8 %	4.2 %	-
Si-CZ	64	95.3 %	4.7 %	-
B/C S: C7 F	26	0220/	1670/	
SI-CZ E	20	03.3 70 86 7 0/	13 8 0/	-
SI-CZ I	29 40	00.2 70 00.5 %	Q 5 %	-
	42	07.0.0/	2 1 0/-	-
DOS D/C	70 26	100 0 %	2.1 /0	-
DOSE	20 19	QA A 0/2	56%	-
DOSIL	16	93.8 %	63%	-

Table 1: Collector distribution by sample area, material, and array (regime). Data as of January 2009.

Final images for the catalog are labeled with sample number, material, and array designation (Fig.1).

**Catalog Results:** Table 1 illustrates a size distribution of the cataloged samples by fraction of sample area, within each material and regime. There are specific exclusions to this presentation (not all of the collection has been evaluated for regime/area measurement), but it is useful in estimating samples available for allocation. The percentage of the collection represented by these exclusions is 57% by numbers of samples (many small fragments are not represented). Nevertheless, a substantial percent of area has been catalogued (Table 2).

The total collector material on the Genesis spacecraft was 1,672,944 mm2 (not including germanium collectors). Total percentage of cataloged array material by area is 18% (as of January 2009).



Fig. 1. Examples of cataloged array fragments (clockwise from upper left): SOS with clean, unscratched surface, AuOS with a heavily scratched surface, AlOS with minor scratches on surface, CZ-Si with dusty surface. SOS and AuOS have 5 mm scale bars, AlOS has a 10 mm scale bar, and CZ-Si has a 2.5 mm scale bar.

**References:** [1] Allton J.H. *et al.* (2005) LPS XXXVI, Abstract #2083. [2] Burnett D.S. *et al.* (2003) Spa. Science Rev., 105:509-534.

MATERIAL	ARRAY	FLOWN AREA (mm2)	AREA CATALOGED (mm2)	TOTAL CATALOGED (%)
GAD	B	25108	10976.0	21.0
	C	25108	101474	21.9
SAP	H	25108	1214/.4	48.4
	E I	25108	2796.6	46.4
	D	21205	2790.0	11.1
	B	25108	33690.2	59.6
SOS	н	25108	1/1878 5	50.3
505	E	25108	16078.6	64.0
	I	25100	0542.6	28.0
	L B	25108	9542.0	38.0
	D C	40400	30110.4	42.0
A105	<u>с</u>	21205	14747.9	47.0
1105	Б	37461	14/4/.0	47.0
-	I	25108	7002 7	31.8
	B	23108	1992.1	51.0
	C	40499	31952.1	48.9
AuOS	Н	62167	19060.8	30.7
	Е	43738	29398.4	67.2
	L	43336	6744.4	15.6
	В	12353	6068.3	49.1
	С	0	0.0	0.0
CC0-	Н	0	0.0	0.0
AuOS	Е	0	0.0	0.0
	L	0	0.0	0.0
	В	56493	3123.2	
	С	112986	5125.2	1.8
CZ Si	Н	43939	2219.0	5.1
	Е	56493	2415.7	4.3
	L	56493	2426.7	4.3
	В	125540	4580 7	
	C	100432		2.0
FZ Si	H	106709	1846.8	1.7
	E	106709	2412.8	2.3
	L	138094	1192.9	0.9
	B	18831	1502.9	4.0
DOS	С и	18831	522.7	4.0
003	п Е	25108	985.8	2.1
	L	25108	730.4	2.9

Table 2. Comparison of total flown array collector material to area cataloged. Data as of January 2009.