

RECENT OPTICAL AND SEM CHARACTERIZATION OF GENESIS SOLAR WIND CONCENTRATOR DIAMOND-ON-SILICON COLLECTOR. J. H. Allton¹, M. C. Rodriguez², P. J. Burkett³, D. K. Ross³ and C. P. Gonzalez³ and K. M. McNamara¹, ¹NASA/Johnson Space Center, 2101 NASA Parkway, Mail Code KT, Houston, TX 77058, USA, Judith.h.allton@nasa.gov, ²ESGC Geocontrol Systems- ESCG at NASA/JSC, ³Jacobs- ESCG at NASA /JSC.

Introduction: One of the 4 Genesis solar wind concentrator collectors was a silicon substrate coated with diamond-like carbon (DLC) in which to capture solar wind. This material was designed for analysis of solar nitrogen and noble gases [1, 2]. This particular collector fractured during landing, but about 80% of the surface was recovered, including a large piece which was subdivided in 2012 [3, 4, 5]. The optical and SEM imaging and analysis described below supports the subdivision and allocation of the diamond-on-silicon (DOS) concentrator collector.

Description of collector 60000: Fig. 1 shows the largest piece of the concentrator DOS collector, as recovered in Utah. This piece was located at the focal point of the concentrator; thus, having the greatest concentration of solar ions. Additionally, this piece had two areas inadvertently not covered by the carbon coating and, thus exposing the silicon to capture solar ions. The exposed silicon, set up a potential opportunity to measure solar carbon. Fig. 2 shows sample 60000 prior to subdivision.

Typical post-landing particulate contamination. Optical imaging of 60000 reveals glass microsphere shards and carbon fibers (both return capsule structural materials), dried droplets, miscellaneous fibers, smears and particles. Near the frame attachments, on the silicon “heel” and “toe” surfaces, smears of gold-colored material are noted (Figs. 3 & 4). A brief survey of related fragment, 60737, was undertaken via SEM (JEOL 7600F). Most abundant particles were gold (with nickel and/or aluminum) and GaZnAl-oxide bearing paint. Less abundant particles consisted of silicate glass, germanium metal, stainless steel, and terrestrial soil.

Evidence of irradiation damage near focal point silicon. Optical imaging revealed a correlation of “blueness” and presence of bubble texture (Fig. 5). No gradient was noted across “heel”. Bubble texture is not observable on “toe”. Estimated flux gradient is 20X near focal point vs 6X near outer radius (Wiens, personal communication).

Imaging after subdivision: Fig. 6 shows solar wind surface after subdivision by laser scribe/cleaving. The subdivision process [4, 5] produces silicon/silicon oxide debris which gets onto the solar wind surface (Fig. 7) and needs to be removed. Further imaging of the subdivided surfaces is in progress.

References:

- [1] Nordholt J. E. *et al* (2003) *Space Sci. Rev.*, **105**, 561-599. [2] Jurewicz A. J. G. *et al.* (2003) *Spa. Sci. Rev.*, **105**, 535-560 (2002), [3] Rodriguez *et al* (2009) *LPS XL*, Abst. #1337, [4] Burkett, P. J. *et al.* (2013), *LPS XLIV* [5] Lauer H. V. *et al* (2013) *LPS XLIV*.




Fig. 1. False color image of DOS collector fragment 60000 mounted in frame and location of frame shadow. Green areas show solar-wind-exposed silicon.



Fig. 2. Fragment 60000 color-enhanced to show increased blueness of silicon areas near focal point, presumably due to irradiation. The bright areas are silicon, called “heel” and “toe” of sock shape.



Fig. 3. Silicon “heel” showing frame shadow and gold-colored smears.




Fig. 4. Silicon "toe" showing gold-colored smear and debris.




Fig. 5. Bubble texture on blue areas of silicon. Bubble features are micrometer diameter.



Fig. 6. Post-subdivision solar wind surface.



Fig. 7. Subdivision process debris added near edges.